

BREATHING RESIN FILM

Patent Number: JP7118431
Publication date: 1995-05-09
Inventor(s): YAMAMOTO KOJI; others: 01
Applicant(s): MITSUBISHI CHEM CORP
Requested Patent: ☐ JP7118431
Application Number: JP19930283852 19931019
Priority Number(s):
IPC Classification: C08J9/00; C08F210/16; C08K3/00; C08L23/08
EC Classification:
Equivalents: JP3109056B2

Abstract

PURPOSE: To obtain the title film which is useful as a packaging material or liquid-sealing material such as hygienic napkin because of its excellent elastic recovery and high nerve by drawing a film made of a resin composition comprising a specifically constituted resin and a specific amount of inorganic filler under specific conditions.

CONSTITUTION: 100 pts.wt. of the resin composition containing (A) 50-99wt.% of ethylene-alpha-olefin copolymer of 0.01-20g/10min MFR, 0.860-0.925g/cm³ density prepared by copolymerization of 40-98wt.% of ethylene and 60-2wt.% of an alpha-olefin of 3 to 30 carbon atoms using a metallocene catalyst, (B) 50 to 1wt.% of an ethylenic resin of 0.01-20g/10min MFR, 0.880-0.935g/cm³ density are mixed with 25 to 500 pts.wt. of an inorganic filler of less than 10μm average particle size, 0.1-0.7g/cm³ and the composition is made into film. Then, the resin film is drawn at a temperature lower than the melting point of component A to give the objective film of 1,800-30,000g/m². 24 hours moisture permeability.

Data supplied from the esp@cenet database - I2